

Traffic paint

Traffic paint "Kontur"

"Kontur" traffic paint is designed to be used with glass beads for marking roads with insufficient lighting. It is based on acrylic resin with the mix of solvents, composition of which guarantees quick drying and long-lasting stable whiteness. It is applied onto a dry and clean surface at the temperature of not less than 5 °C.

Road marking performance (glass beads consumption - 250 gr/m²)

Qd >100

RL > 250

SRT ≥ 0.50

Application data

Pneumatic or airless machinery

Paint filter 60 mesh

Temperature: from +5°C to +30°C

Humidity: no more than 85%

Specification

Density: 1.6 ± 0.05

Solid content: 77 ± 2%

Whiteness: 91-93% (white), ≥ 65% (yellow), ≥ 30% (orange), ≥ 10% (black)

Drying time: 10 min at 20°C and 65% humidity

Recommended glass beads consumption: 200-250 gr/m²

Recommended paint consumption: 600-700 gr/m²

Package: 30 kg pail

Available paint colors: white, yellow, orange, black.



Traffic paint "Kontur ECO"

"Kontur Eco" is the ecologically clean road marking material of excellent quality. It is solvent-based paint with quick drying time and long-lasting stable whiteness. It's proven by BAST (German Federal Highway Research Institute) certification compliance.

Road marking performance (glass beads consumption 250 gr/m²)

Qd >100

RL > 250

SRT ≥ 0.50

Application data

Pneumatic or airless machinery

Paint filter 60 mesh

Temperature: from +5°C to +35°C

Humidity: no more than 85%

Specification

Density: 1.6 ± 0.05

Solid content: 76 ± 1%

Whiteness: 91-93% (white), ≥ 65% (yellow), ≥ 30% (orange), ≥ 10% (black)

Drying time: 15 min at 20°C and 65% humidity

Recommended glass beads consumption: 200-250 gr/m²

Recommended paint consumption: 600-700 gr/m²

